

Cook & Hold Oven

Model 1750-TH

Original Cook & Hold Ovens produce better food quality and higher yields with built-in savings.

Gentle, radiant Halo Heat® technology evenly surrounds food without the use of extremely hot elements, added humidity or fans. This controlled, uniform heat maintains precise temperatures throughout the cooking and holding process—improving food quality and extending hold times.

Cook by time or probe with Simple or Deluxe controls. Probes sense internal product temperature and automatically convert the oven from cook mode to hold mode once set parameters have been reached.

Labor-free, overnight cooking and effortless operation reduces labor costs and increases productivity.

Place anywhere with a ventless, waterless design. Lower costs with energy efficient operation and no water hookups or traditional kitchen hood required. All Alto-Shaam Cook & Hold Ovens are EPA 202 Certified ventless.

Advanced controls – designed intentionally simple – feature an intuitive, user-friendly interface and programmable recipes to ensure consistency with each cook.

ChefLinc™, cloud-based remote oven management software, streamlines processes and maximizes profits with data-driven insights [Deluxe model only].

ISO 9001:2015-certified

Standard Features

- Casters (two [2] rigid, two [2] swivel with brake)
- Single-point, straight removable probe
- Drip tray and drip pan with drain
- Programmable, touchscreen control on Deluxe model
- HACCP data collection on Deluxe model
- Programmable control on Simple model
- Easy recipe upload/download via USB port
- SureTemp™ heat recovery on Deluxe model
- Two [2] stainless steel side racks with ten [10] pan positions spaced 35mm on centers
- Removable exterior drip tray



10 GN 1/1 — 530mm x 325mm x 65mm

20 GN 1/2 — 265mm x 325mm x 65mm

**CAPACITY
per Cavity**

Maximum weight per cavity: 45 kg
Maximum volume cavity: 71 liters

Six [6] shelves [3 per cavity] included. Additional shelves required for maximum capacity.



CE EAC

IP X4



Lifetime Warranty

On all Cook & Hold heating elements (excludes labor)

ALTO-SHAAM



Shown with Deluxe control



Shown with Simple control

1750-TH

Configurations (select one each)

Models

- Simple
 - HACCP option
- Deluxe
 - Ethernet option (5032090)

Door Choice

- Right hinged, solid door, standard
- Right hinged, window door
- Left hinged, solid door
- Left hinged, window door

Electrical

- 230V, 1PH
- 380-415V, 3Ph

Casters and Legs

- 89mm casters, two [2] rigid two [2] swivel with brake, option (5027133)
- 127mm casters, two [2] rigid two [2] swivel with brake, option, (5027112)
- 152mm legs, set of four [4] (5032092)
- 152mm seismic legs, set of four [4] (5032093)

Optional Accessories (select all that apply)

Bumper and Handles

- Full perimeter bumper
- Push/Pull handle kit

Additional Probes

- Sous vide probe (PR-36576)
- T-handle probe, up to six [6] with Deluxe per cavity (PR-46998)
- Straight probe, up to six [6] with Deluxe per cavity (qty two [2] included with oven) (PR-46999)

Drip Pans, Shelves, Holders

- Drip pan with drain (5027713)
- Drip pan, without drain (1034370)
- Increased capacity exterior drip pan (5030664)
- Shelf, stainless steel (SH-2324)
- Carving holder, prime rib (HL-2635)
- Carving holder, steamship [cafeteria round] (4459)

Cleaners

- Alto-Shaam, non-caustic cleaner one [1] 1-liter bottle (CE-46828)
- Alto-Shaam, non-caustic cleaner six [6] 1-liter bottles (CE-46829)

Accessories, misc.

- Door lock with key (5028755)


Cook & Hold Oven

Model 1750-TH








DIMENSIONS

OVERALL HEIGHT: 1750-TH	
Accessory	mm
127mm caster	1474
89mm caster	1448
152mm leg (min)	1420
152mm leg (max)	1477
152mm seismic leg (min)	1444
152mm seismic leg (max)	1506



Shown with Simple control and 89mm casters



Interior (H x W x D) Per Cavity	Net Weight	Ship Dimensions (L x W x H)	Ship Weight
510mm x 559mm x 673mm	200 kg	991mm x 991mm x 2007mm	240 kg



CLEARANCE

- Top: 51mm
- Left: 51mm
- Right: 51mm
- Back: 76mm



CHECK FIRST

The oven must be installed level.
The oven must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

Cook & Hold Oven

Model 1750-TH



Heat of rejection

1750-TH	Heat Gain qs, BTU/hr	Heat Gain qs, kW
	1,825	0.53



Cooking temperature range:

94°C–163°C

Holding temperature range:

29°C–96°C



1750-TH	V	Ph	Hz	Awg	IEC	A	Breaker (A)	kW	Plug Configuration	Certification	
208–240V**	208	1	60	8	—	29	30 UL 50 CSA	6.3	Alto-Shaam offers a number of readily available cord and plug configurations. Contact factory for options.		
	240	1	60	8	—	35	50	8.3			
230V	230	1	50/60	8	—	33	63	7.6			
	230	1	50/60	8	—	22	32	5.1*			
380–415V	380	3	50/60	10	2.5	18	32	7.0			
	415	3	50/60	10	2.5	20	32	8.2			

Electrical connections must meet all applicable federal, state, and local codes.

*Reduced wattage configuration.

**Dedicated circuit required.

CONTACT US

W164 N9221 Water Street | Menomonee Falls, Wisconsin 53051 | U.S.A.
 Phone: 262.251.3800 | 800.558.8744 U.S.A./Canada | Fax: 262.251.7067 | alto-shaam.com